

What is claimed is:

1. (Previously Presented) An apparatus adapted for engagement with a concrete fillable formwork wall having elongated, octagonal tubular form elements consisting of:

a wall panel, wherein the wall panel consists of one substantially flat wall and two wall panel ends and a male engagement portion at each end, wherein each male engagement portion consists of a fin, wherein both fins extend from one side of the wall panel, and wherein each fin is adapted to engage a matching female engagement portion on one elongated, octagonal tubular form element;

whereby the engagement of the male engagement portions on the wall panel to matching female engagement portions of two elongated, octagonal tubular form elements forms a triangular closed area between the two elongated, octagonal tubular form elements and the wall panel, and

whereby the engagement of the wall panel forms a substantially flat exterior wall surface along the elongated, octagonal tubular form elements to which the wall panel is engaged.

2. (Withdrawn) The apparatus of Claim 1, wherein the male engagement portion on each end of the insert panel comprises one or more of an engagement fin, projection, finger or lip.

3. (Withdrawn) The apparatus of Claim 2, wherein the male engagement portion on each end of the insert panel is T-shaped, P-shaped, H-shaped, or Y-shaped.

4. (Canceled)

5. (Withdrawn) The apparatus of Claim 1, wherein the insert panel has two substantially straight or flat surfaces residing at a perpendicular angle relative to each other to form a corner and is a formwork corner panel,

wherein the male engagement portions at each end extend from a same side of the corner,

wherein each male engagement portion has a first projection and an integral second projection,

wherein the first projections at the ends extend substantially perpendicular to each other, and

wherein the second projections at the ends extend substantially parallel to each other.

6. (Cancelled)

7. (Withdrawn) The apparatus of Claim 5, wherein the insert panel has perforations.

8. (Previously Presented) The apparatus of Claim 1, wherein the apparatus forms substantially flat walls of a building.

9. (Withdrawn) The apparatus of Claim 5, wherein the apparatus forms substantially flat walls of a building.

10. (Withdrawn) A method of finishing a plurality of elongated, octagonal tubular form elements to form a substantially flat wall, comprising the step of mating a male engagement portion of an end of an insert panel of Claim 1 with a female engagement portion of at least one of an elongated, octagonal tubular form element.

11. (Withdrawn) A method of finishing a plurality of elongated, octagonal tubular form elements to form a substantially flat wall, comprising the step of mating a male engagement portion of an end of an insert panel of Claim 2 with a female engagement portion of at least one of an elongated, octagonal tubular form element.

12. (Withdrawn) The apparatus of Claim 1, wherein the male engagement portion on each end of the insert panel is T-shaped, P-shaped, H-shaped, or Y-shaped.

13 -18. (Cancelled)